

# **55-110**Non-clean/Non-sterile Latex (NRL) RABS/Isolator Gloves

# NRL RABS/Isolator gloves, for hand protection with heightened tear and abrasion resistance

Port size: 305mm/12"
Thickness: 0.51mm/20 mil

- Sustained protection: AlphaTec® NRL RABS and Isolator Gloves 55-110 meet EN 388 Level 2 standards for tear and abrasion resistance
- Improved dexterity: Medium-level thickness offers these isolator gloves greater dexterity, making them ideal for daily repetitive applications
- Limited contamination risks: As they are unlined, absorption of chemical substances and subsequent contamination is less likely, while their translucent design facilitates cleaning

#### **KEY FEATURES & BENEFITS**

- EN 388 compliance: Elevated resistance against tears and abrasion
- Medium thickness: Enhanced dexterity, for easier parts handling
- **Unlined:** Reduced contamination risks and easy to clean







# 55-110

Non-clean/Non-sterile Latex (NRL) RABS/Isolator Gloves

### **TECHNICAL DATA SHEET**

Product Reference	55-110
Material	Natural Rubber Latex
Color	Natural
Shape	Ambidextrous
External Glove Surface	Smooth
Cuff Style	Beaded
Storage Instructions	Store in a dry and dark environment, temperature of 5°C to 22°C. Retain in original packaging when not in use.
Available Sizes	10
Temperature Range	From -30°C to 50°C
Shelf Life	Three (3) years from date of manufacture.
Standards	CE 0493, EN 388:2016 +A1:2018, EN ISO 21420:2020, EN ISO 21420:2020, EN ISO 374-1:2016, EN ISO 374-5:2016, EN ISO 374-1:2016, EN ISO 374-5:2016, EN 420:2003 + A1:2009, Category III





# 55-110 Non-clean/Non-sterile Latex (NRL) **RABS/Isolator Gloves**

#### **PHYSICAL PROPERTIES**

	Typical Values	Testing Method
Typical Length (mm/in)	813mm / 32"	EN 455-2
Port Size	305mm/12"	
Target Single Wall Palm Thickness (mm/mil)	0.51 mm / 20 mil	EN 455-2
Target Single Wall Cuff Thickness (mm/mil)	0.51 mm / 20 mil	EN 455-2

### PROTECTION AGAINST MECHANICAL RISKS, EN 388:2016+A1:2018

Risk	Performance level
Abrasion Resistance	Level 2
Blade Cut Resistance	Level O
Tear Resistance	Level 2
Puncture Resistance	Level O

#### ORDERING INFORMATION

	PORT SIZE	12"/305mm
	SIZE	10
55-110	REORDER NO.	55110010

#### **Performance Standards and Regulatory Compliance**

**C** € 0493







(女)

#### For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

## Asia Pacific Region

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

#### North America Region

Ansell Healthcare Products LLC US T: +1 800 800 0444 US F: +1 800 800 0445 CA T: +1-800-363-8340

#### Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

#### Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

#### UK

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890







Ansell,  $^{\circledR}$  and  $^{\intercal}$  are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking  $^{\circledR}$  2024 Ansell Limited. All Rights Reserved.

