

BioClean™ Clearview Sterile Looped Visor Facemask VFM210-L

Sterile looped visor face mask, offering advanced bacterial and particle filtration efficiency

- Advanced defenses: The BioClean[™] Clearview Sterile Looped Visor Facemask VFM210-L delivers high bacterial and particle filtration efficiency, for protection of your cleanroom environment you can depend on
- Enhanced features: This sterile face mask features a looped design and optically clear visor, with an anti-fog coating, to enable maximized vision
- Increased comfort: The BioClean[™] Clearview Sterile Looped Visor Facemask VFM210-L also offers users breathable comfort

Key Features and Benefits

- High bacterial and particle filtration efficiency: Optimized protection
- Anti-fog-coated visor: Unhindered, distortion-free vision

Industries

- Controlled and Critical Environments
- Laboratory and Research
- Production and Manufacturing

Recommended For

- Biotechnologies Blending operations
- Clean room cleaning and preparing
- Medical Device Manufacturing
- Preparing pharmaceutical products
- Semiconductor manufacturing
- White goods assembly







BioClean[™] Clearview Sterile Looped Visor Facemask VFM210-L

TECHNICAL DATA SHEET

PRODUCT INFORMATION

| Material | Polypropylene Polyethylene | | |
|-------------------------------|---|--|--|
| Audit Standards | Manufacturing QMS Audit Standards ISO 9001 | | |
| Standards | ISO 2859, ISO 9001:2015 | | |
| Packaging Overview | One piece per sealed inner PE bag; 25 inner bags per sealed outer PE bag; four outer bags per lined carton (100 pieces) | | |
| Country Of Origin | China | | |
| Sterilization Method | Gamma Irradiation | | |
| Sterilization Minimum Dose | 25kGy | | |
| Sterility Assurance Level | 10-6 | | |
| Storage Instructions | Store in a dry, cool place (<40°C) away from direct sunlight and fluorescent light. | | |
| Shelf Life | Five (5) years from date of manufacture | | |

PHYSICAL PROPERTIES

| Color | White |
|---------------------------|---|
| String Type | Headloop |
| Overall Dimensions | WIDTH (± 5mm): 210mm HEIGHT (± 5mm) : 95mm |
| Inner Facing Layer | Non-woven polypropylene/polyethylene (hydrophilic) |
| Filtration Layer | Meltblown polyester |
| Outer Layer | Non-woven spunbonded polyester (hydrophobic) |
| Fastenings | Non-latex polyurethane loops with plastic clip fastener |
| Noseband | Plastic coated steel |





PERFORMANCE INFORMATION

| Cleanroom Class | Class 10/ISO Class 4 & EU GMP Grade A/B and other sterile cleanrooms |
|------------------------------------|--|
| Particle Filtration Efficiency | 89.3% @0.1 micron |
| Bacterial Filtration Efficiency | 92.3% @0.3 micron |
| Viral Filtration Efficiency | 93.8% @3.0 micron |
| Differential Pressure | 3.8mm H₂O/cm⊠ |

ORDERING INFORMATION

| | SIZE | Looped with blue clip fastener |
|----------|-------------|--------------------------------|
| VFM210-L | REORDER NO. | VFM210-L |

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region North America Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center T: +603 8310 6688 F: +603 8310 6699

Ansell Healthcare Products LLC US T: +1 800 800 0444 US F: +1 800 800 0445 CA T: +1-800-363-8340

Australia

UK Latin America & Caribbean Region

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

Ansell Nitritex T: +44 1638 663338 F: +44 1638 668890

Ansell, [®] and [™] are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

