

Protective gloves with dual-layer design, suitable against opioids and other hazardous substances

- **Specialized protection:** The MICROFLEX® ApexPro™ XP100 APXP12 gloves provide reliable protection against opioids and other hazardous substances — the gloves have been tested against fentanyl and gastric acid (vomit), to simulate real-world overdose conditions
- **Dual-layer design:** Features a dual-layer, dual-color design (black exterior, grey interior)
- **Low AQL:** These nitrile gloves' low (0.65) AQL means they provide superior barrier protection
- **Easy visibility:** The black exterior and grey interior makes it easier to see potentially hazardous powders, so wearers know when to change gloves
- **Supporting skin health:** These gloves are triple-washed and have a true pH-balanced interior coating to reduce irritation and support skin health



Industries

- Chemical
- Correctional Facilities
- Emergency Medical Services
- Healthcare
- Law Enforcement
- Life Sciences
- Machinery and Equipment
- Maintenance
- Manufacturing
- Recycling and Waste Disposal
- Transportation

Recommended For

- Administering drugs
- Standard patient examinations
- Emergency services
- Overdose situations
- Equipment repair and maintenance
- Inspection, selecting, checking parts
- Laboratory analysis
- Raw material sample collection
- Light assembly tasks
- Disposal of waste (trash, biohazard and linens)
- Sample taking and processing
- Maintenance

TECHNICAL DATA SHEET

	Product Information
Material	Nitrile
External Glove Surface	Fully Textured
Audit Standards	ISO 13485, ISO 9001
Product Certification	Medical Device Regulation (EU) 2017/745 Class I, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks, ASTM D6319, FDA21 CFR 177-2600-US Food Contact Approved, NFPA 1999:2018, ISO 13485, ISO 9001
Packaging Overview	100 gloves per box; 10 boxes per case; 2XL and 3XL: 80 gloves per box; 10 boxes per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	China
Product Segmentation	High Risk
Antistatic	Not Tested
Silicone Free	Not Tested


PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	300 / 11.8		ASTM D6319
Freedom from Holes (Inspection level I)	0.65 AQL		ISO 2859-1
Palm Thickness (mm/mils)	0.15 / 5.9		ASTM D6319
Finger Thickness (mm/mils)	0.21 / 8.3		ASTM D6319
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	22	20	ASTM D412 & D573
Elongation at Break (%)	≥550	≥500	ASTM D412

ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)	XXXL (11.5 - 12)
Product Code	APXP12-1X	APXP12-1	APXP12-2	APXP12-3	APXP12-4	APXP12-5	APXP12-6

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region
Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region
MY: +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

North America Region
Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region
BR: +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

Australia
Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia
Ansell PYC
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

