

Diamond Grip Plus® DGP-350

Latex Exam Glove

Latex exam gloves with exceptional fit and feel for extended wear

- Secure grip: MICROFLEX® Diamond Grip Plus™ DGP-350 latex medical exam gloves are fully textured, for a secure grip in both wet or dry environments
- Tactile sensitivity: Excellent tactile sensitivity ensures precise handling during patient care or when handling delicate products or laboratory instruments
- Comfortable and elastic fit: Superior elasticity means gloves move with you for greater comfort
- Outstanding quality: Exceeds standards for tensile strength, elasticity/elongation and other quality standards for average latex gloves

*CAUTION: This product contains natural rubber latex, which may cause allergic reactions



Industries

- Food Processing
- Life Sciences
- Healthcare
- Utilities
- Warehousing

Recommended For

- Equipment, maintenance and repair
- All food processing, applications that have food contact
- Sample taking and processing
- Extra comfort during long, sustained procedures
- Standard patient examinations



TECHNICAL DATA SHEET

| | Product Information |
|------------------------|---|
| Material | Natural Rubber Latex |
| External Glove Surface | Fully Textured |
| Audit Standards | EN ISO 13485:2012 |
| Product Certification | ASTM D3578, EN ISO 21420:2020, FDA21 CFR 177-2600-US Food Contact Approved, US QSR/FDA 510(k) Medical Examination Grade |
| Packaging Overview | 100 gloves per dispenser 10 dispensers per case 1000 gloves per case |
| Storage Instructions | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition. |
| Country Of Origin | Malaysia |
| Antistatic | Not Tested |
| Silicone Free | Yes |

PHYSICAL PROPERTIES

| | Typical | Testing Method | |
|---|---------------------|---------------------|-------------------|
| Length (mm/inches) | 245 / | ASTM D3767,EN 420 | |
| Freedom from Holes (Inspection level I) | 1.5 A | ASTM D5151,EN 455-1 | |
| Palm Thickness (mm/mils) | 0.14/5.5 | | ASTM D3767,EN 420 |
| Finger Thickness (mm/mils) | 0.16, | ASTM D3767,EN 420 | |
| | BEFORE AGING | AFTER AGING | |
| Ultimate Tensile Strength (MPa) | 22 | 20 | ASTM D412 & D573 |
| Elongation at Break (%) | ≥ 700 | ≥ 600 | ASTM D412 |
| Force at break (N) | 9 | 9 | EN 455-2 |

ORDERING INFORMATION

| Size | XS (5.5 - 6) | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) |
|--------------|--------------|-------------|-------------|-------------|---------------|
| Product Code | DGP-350-XS | DGP-350-S | DGP-350-M | DGP-350-L | DGP-350-XL |

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region MY +603 8310 6688 apac.medical@ansell.com CN: +86 21 38275000 infochina@ansell.cor JP: +813 5549 8151

North America Region Ansell Healthcare Products LLC T: +1800 800 0444 F: +1800 800 0445

Latin America & Caribbean Region BR +55 (11) 3356-3100 latam.medical@ansell.com MX: +52 442 296 2050 latam.medical@ansell.com CO: +57 1 288 3247 latam.medical@ansell.com

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578 Russia

Ansell PYC Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

