

LIFESTAR EC<sup>™</sup> LSE-104 High Risk Exam Nitrile Gloves

# Dual-layer first responder gloves, offering barrier protection against opioids and chemical hazards

- Reinforced protection: MICROFLEX<sup>®</sup> Lifestar EC<sup>™</sup> LSE-104 EMS gloves' duallayer, dual-color design offers first responders and healthcare workers double-layered hand protection
- Specialized resistance: Tested against Fentanyl and gastric acid (vomit) in real-world overdose simulations, these gloves ensure advanced protection for medical professionals
- Enhanced grip: These medical gloves' non-stick/non-foaming properties and textured fingertips ensure confident grip performance, for handling bandages, liquids, medical tape, etc.
- Certified performance: Satisfying NFPA 1999 Emergency Medical Glove Requirements and boasting chemical splash resistance certification, these nitrile exam gloves offer wearers proven protection

### Industries

- Healthcare
- Emergency Medical Services



#### **Recommended For**

- Administering drugs
- Inspection, selecting, checking parts
- Sample taking and processing
- Transferring liquids and solids
- Emergency services
- Standard patient examinations
- Overdose situations



# **TECHNICAL DATA SHEET**

	Product Information
External Glove Surface	Textured Fingers
Audit Standards	ISO 13485
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case *90 gloves per dispenser (SizeXXXL) *900 gloves per case (Size XXXL)
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Malaysia
Product Segmentation	High Risk
Antistatic	Yes EN1149

#### **PHYSICAL PROPERTIES**

	Typical	Testing Method	
Length (mm/inches)	≥ 280 / 11.0		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	0.65 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.15 / 5.5		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.22 / 8.7		ASTM D3767,EN 420
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	27	22	ASTM D412 & D573
Elongation at Break (%)	650	550	ASTM D412
Force at break (N)	14	11	EN 455-2

#### **ORDERING INFORMATION**

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)	XXXL (11.5 - 12)
Product Code	LSE-104-S	LSE-104-M	LSE-104-L	LSE-104-XL	LSE-104-2XL	LSE-104-3XL

#### **Performance Standards and Regulatory Compliance**



For additional information visit us at www.ansell.com, or call us at

#### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

## **Asia Pacific Region** MY +603 8310 6688 apac.medical@ansell.com CN: +86 21 38275000

infochina@ansell.cor JP: +813 5549 8151 ansell.com info.m

North America Region Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445

#### Latin America & Caribbean Region BR +55 (11) 3356-3100 latam.medical@ansell.com MX: +52 442 296 2050 latam.medical@ansell. CO: +57 1 288 3247 latam.medical@ansell. ell.com

Australia Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

Russia Ansell PYC Ten. +7 495 258 13 16

Ansell, <sup>®</sup> and <sup>™</sup> are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

ell.com

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

