

Strong nitrile gloves with extra thickness for additional protection

- **Tear-resistant:** MICROFLEX™ N21 disposable gloves feature an extra-thick nitrile design — 5 mil thick at the palm, these strong, blue nitrile gloves resist tearing even during the toughest jobs
- **Secure grip:** Excellent for active jobs which require workers to firmly grip tools, equipment and other objects, these gloves are fully textured to prevent accidental drops
- **Food handling compliance:** These latex-free exam gloves are suitable for a wide range of food-handling applications, particularly for food processing workers in contact with rough edges like bones or frozen foods
- **Medical exam grade:** These gloves are also medical exam grade, and can be used by doctors, nurses, physician's assistants and other healthcare or dental professionals in need of sturdy, durable exam gloves for jobs like equipment cleaning or office disinfection



Industries

- Food Processing
- Life Sciences
- Healthcare
- Fire and Rescue

Recommended For

- All food processing, applications that have food contact
- Sample taking and processing
- Standard, moderate risk examination procedures
- Protection from Type I latex allergy in HCW's or patients
- Equipment repair and maintenance
- Assembly of parts

TECHNICAL DATA SHEET

Product Information	
Material	Nitrile
External Glove Surface	Fully Textured
Audit Standards	EN ISO 13485:2012
Product Certification	ASTM D6319, Health Canada, REACH, California Proposition 65, FDA 21CFR177.2600, ISO 10993-5, 10, 23, ASTM F1671, ISO 11737
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case 2XL: 90 gloves per dispenser 10 dispensers per case 900 gloves per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Malaysia
Product Segmentation	Multi-Purpose
Antistatic	Not Tested
Silicone Free	No

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	240 / 9.45		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	4.7		ASTM D3767,EN 420
Finger Thickness (mm/mils)	5.5		ASTM D3767,EN 420
	BEFORE AGING	AFTER AGING	
Elongation at Break (%)	≥ 500	≥ 400	ASTM D412

ORDERING INFORMATION

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	2XL (10.5-11)
Product Code	N211	N212	N213	N214	N215

Performance Standards and Regulatory Compliance



ISO 10993-10 ISO 10993-23

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV

T: +32 (0) 2 528 74 00

F: +32 (0) 2 528 74 01

Asia Pacific Region

MY: +603 8310 6688

apac.medical@ansell.com

CN: +86 21 38275000

infochina@ansell.com

JP: +813 5549 8151

info.medical.jp@ansell.com

North America Region

Ansell Healthcare Products LLC

T: +1 800 800 0444

F: +1 800 800 0445

Latin America & Caribbean Region

BR: +55 (11) 3356-3100

latam.medical@ansell.com

MX: +52 442 296 2050

latam.medical@ansell.com

CO: +57 1 288 3247

latam.medical@ansell.com

Australia

Ansell Limited

T: +61 1800 337 041

F: +61 1800 803 578

Russia

Ansell PYC

Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

