MICROFLEX™

# Onyx® N64

## Black, Nitrile Exam Glove with Textured Fingers

# Multipurpose black nitrile exam gloves, offering exceptional chemical splash protection

- **Advanced protection:** Made using proprietary TNT™ Chemical Splash Resistance Technology, MICROFLEX™ Onyx™ N64 nitrile medical exam gloves offer chemical splash resistance against a wide range of hazards
- **Elevated comfort:** These exam gloves soft nitrile formulation delivers exceptional comfort, while ensuring durability
- **Black glove:** Creates contrast while hiding the appearance of oils, bodily fluids and other stains
- **Genuine versatility:** Their mid-duty profile ensures they offer hand protection for a wide range of industries and applications
- **Enhanced grip:** These nitrile disposable gloves also feature textured fingers, for secure, consistent grip performance



### Industries

- Automotive
- Healthcare
- Dental

### Recommended For

- Standard, moderate risk examination procedures
- Protection from Type I latex allergy in HCW's or patients
- Inspection (picking, checking and marking)
- Inspection
- Painting or cleaning tools or robots
- Inspection, selecting, checking parts
- Equipment repair and maintenance
- Body surface checking, marking and touching up

# TECHNICAL DATA SHEET

| | Product Information |
|---|---|
| Material | Nitrile |
| External Glove Surface | Textured Fingers |
| Audit Standards | ISO 13485:2003 |
| Product Certification | ASTM D6319, EU Food Contact Approved, EN ISO 21420:2020, FDA21 CFR 177-2600-US Food Contact Approved, US QSR/FDA 510(k) Medical Examination Grade |
| Packaging Overview | 100 gloves per dispenser<br>10 dispensers per case<br>1000 gloves per case |
| Storage Instructions | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition. |
| Country Of Origin | Malaysia |
| Product Segmentation | Multi-Purpose |
| Antistatic | Not Tested |
| Silicone Free | Yes |

## PHYSICAL PROPERTIES

| | Typical Values | | Testing Method |
|---|---|---|---|
| Length (mm/inches) | 245 / 9.65 | | ASTM D3767,EN 420 |
| Freedom from Holes (Inspection level I) | 1.5 AQL | | ASTM D5151,EN 455-1 |
| Palm Thickness (mm/mils) | 0.09 / 3.5 | | ASTM D3767,EN 420 |
| Finger Thickness (mm/mils) | 0.14 / 5.1 | | ASTM D3767,EN 420 |
| | **BEFORE AGING** | **AFTER AGING** | |
| Ultimate Tensile Strength (MPa) | 16 | 14 | ASTM D412 & D573 |
| Elongation at Break (%) | ≥ 500 | ≥ 400 | ASTM D412 |

## ORDERING INFORMATION

| Size | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) | XXL (10.5 - 11) |
|---|---|---|---|---|---|
| Product Code | N641 | N642 | N643 | N644 | N645 |

## Performance Standards and Regulatory Compliance



## For additional information visit us at www.ansell.com, or call us at


**Europe, Middle East & Africa Region**
Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

**Asia Pacific Region**
MY +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

**North America Region**
Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

**Latin America & Caribbean Region**
BR +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

**Australia**
Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

**Russia**
Ansell PYC
Ten. +7 495 258 13 16



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.