

Supreno® EC SEC-375

Durable Nitrile Exam Glove with Extended Cuff and Advanced Barrier Protection

Medical exam gloves with extended chemical splash protection, approved for handling chemotherapy drugs

- Strong formulation: MICROFLEX[®] Supreno[®] EC SEC-375 exam gloves' robust nitrile formulation makes them more durable and resistant to rips, snags and tears
- Specialized protection: Simulating real-world overdose conditions, these gloves are specially tested against gastric acid (vomit) and fentanyl, as well as cytotoxic/chemotherapy drugs*
- Real-world performance: These sturdy medical exam gloves also satisfy NFPA 1999 Emergency Medical Glove Requirements, making them suitable for healthcare professionals, first responders and lab workers
- Low AQL: These medical exam gloves' low 0.65 AQL reinforces their barrier integrity
- Extended protection: Featuring an extended cuff, these gloves offer forearm and wrist protection for medical workers

*see product packaging for details

Industries

- Automotive
- Automotive Aftermarket
- Life Sciences
- Healthcare
- Emergency Medical Services
- **Recommended For**
- Inspection, selecting, checking parts
- Assembly and inspection of components
- Picking and fastening components
- Equipment repair and maintenance
- General Purpose Auto Aftermarket
- Tire rotation & changes
- Animal care feeding and cleanup
- Maintaining lab furniture and equipment
- Sample taking and processing
- Administering drugs
- Raw material sample collection
- Tested for use with chemotherapy drugs
- Extra protection over the wrist and arm
- Higher-risk clinical applications
- Protection from Type I latex allergy in HCW's or patients





TECHNICAL DATA SHEET

	Product Information
External Glove Surface	Textured Fingers
Audit Standards	ISO 13485
Packaging Overview	50 gloves per dispenser 10 dispensers per case 500 gloves per case *40 gloves per dispenser (Size XXXL) *400 gloves per case (Size XXXL)
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Malaysia
Product Segmentation	High Risk
Antistatic	Yes

PHYSICAL PROPERTIES

	Typical	Testing Method	
Length (mm/inches)	295 /	ASTM D3767,EN 420	
Freedom from Holes (Inspection level I)	0.65 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.14 / 5.5		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.22 / 8.7		ASTM D3767,EN 420
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	32	27	ASTM D412 & D573
Elongation at Break (%)	550	500	ASTM D412
Force at break (N)	15	12	EN 455-2

ORDERING INFORMATION

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)	XXL (10.5 - 11)	XXXL (11.5 - 12)
Product Code	SEC-375-S	SEC-375-M	SEC-375-L	SEC-375-XL	SEC-375-XXL	SEC-375-XXXL

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region MY +603 8310 6688 apac.medical@ansell.com CN: +86 21 38275000

infochina@ansell.cor JP: +813 5549 8151 ansell.com info.m

North America Region Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445

Latin America & Caribbean Region BR +55 (11) 3356-3100 latam.medical@ansell.com MX: +52 442 296 2050 latam.medical@ansell. CO: +57 1 288 3247 latam.medical@ansell. ell.com

Australia Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

Russia Ansell PYC Ten. +7 495 258 13 16

Ansell, [®] and [™] are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2024 Ansell Limited. All Rights Reserved.

ell.com

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

