

Ultra One® UL-315

Durable Latex Exam Glove with Extended Cuff

Durable, disposable medical gloves, delivering robust, extended hand protection

- Heightened defenses: These latex medical exam gloves benefit from a thick finger (0.32mm/12.6 mil) and palm (0.25mm/9.8 mil) design, granting them greater strength and durability than standard exam gloves
- Elevated comfort: Thanks to their soft, elastic composition, these thick latex gloves provide wearers with a comfortable fit and feel
- Expanded protection: These gloves are also designed with an extended cuff, offering additional forearm and wrist protection

CAUTION: This product contains natural rubber latex, which may cause allergic reactions



Industries

- Life Sciences
- Machinery and Equipment
- Healthcare

Recommended For

- Unpacking of bulk goods
- Maintaining lab furniture and equipment
- Sample taking and processing
- Transporting raw materials
- Inspection (picking, checking and marking)
- Extra protection over the wrist and arm
- Higher-risk clinical applications



TECHNICAL DATA SHEET

	Product Information		
Material	Natural Rubber Latex		
External Glove Surface	Textured Fingers		
Audit Standards	EN ISO 13485:2012		
Product Certification	ASTM D3578, EN ISO 21420:2020, FDA21 CFR 177-2600-US Food Contact Approved, US QSR/FDA 510(k) Medical Examination Grade, EU Food Contact Approved		
Packaging Overview	50 gloves per dispenser 10 dispensers per case 500 gloves per case		
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.		
Country Of Origin	Malaysia		
Product Segmentation	High Risk		
Antistatic	Not Tested		
Silicone Free	No		

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	300 / 11.8		ASTM D3767,EN 420
Freedom from Holes (Inspection level I) 1.5 AQL		AQL	ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.25 / 9.8		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.32 / 12.6		ASTM D3767,EN 420
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	≥ 32	≥ 20	ASTM D412 & D573
Elongation at Break (%)	≥ 750	≥ 700	ASTM D412

ORDERING INFORMATION

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	UL-315-S	UL-315-M	UL-315-L	UL-315-XL

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region MY +603 8310 6688 apac.medical@ansell.com CN: +86 21 38275000 infochina@ansell.com JP: +813 5549 8151 info.medical.jp@ansell.com North America Region Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445

Latin America & Caribbean Region BR +55 (11) 3356-3100 latam.medical@ansell.com MX: +52 442 296 2050 latam.medical@ansell.com CO: +57 1 288 3247 latam.medical@ansell.com Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578
Russia

Ansell PYC Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Ansell