



## R-068

Fully coated safety gloves designed for impact, cut and liquid protection



Impact Abrasion Protection



Cut Liquid Spray and Splash



Oil



Light Duty

# Fully coated safety gloves designed for impact, cut and liquid protection

- **Advanced defenses:** Developed with F3 Technology™, RINGERS® R068 impact gloves feature a comfortable, dexterous TPR (thermoplastic rubber) design, offering optimal hand coverage
- **Specialized protection:** These hand protection gloves boast fully dipped nitrile coating, granting wearers an effective liquid resistance barrier, for truly reliable personal protection
- **Enhanced features:** Their high-visibility design reinforces wearer protection, while touchscreen-compatible thumb tips, index and middle fingers enable technological interaction without compromising hand safety
- **Strengthened grip:** RINGERS® R068 safety gloves also feature half-dipped palm coating with a sandy finish, offering better grip on wet and dry surfaces, for improved workplace safety



### Industries

- Construction
- Oil and gas
- Manufacturing
- Mining
- Automotive Aftermarket
- Chemical
- Emergency Medical Services
- Machinery and Equipment
- Metal fabrication

### Applications

- Running tools into the wellbore
- Assembly and disassembly of large pipes
- Engagement and release of drill string slips
- Unloading and stacking pipe
- Set-up of pressure manifold and tubing injector head
- General pumping work
- Loading and hauling
- Assembling and mounting components
- Concentration mixing and palletisation
- Hydraulic repair
- Use of binding agents
- Smelting and cleaning of equipment
- Re-fuel oil fluid and diesel
- Tank Cleaning



# R-068

Fully coated safety gloves designed for impact, cut and liquid protection

### Key Features

- **Patented TPR design:** For PPE gloves with strong impact protection
- **Fully dipped nitrile coating:** Liquid resistance and hand protection
- **Touchscreen compatibility:** For consistent protection and usability

### Technologies



**Touchscreen Compatible**

### Performance Standards & Regulatory Compliance



4X44FP

ANSI/ISEA 105-2024



X1XXXX

### Specifications

BRAND   STYLE	DESCRIPTION	Gauge	SIZE	COATING COLOR	PACKAGE
RINGERS® R068	<b>Finishing:</b> Fully Dipped <b>Coating Material:</b> Nitrile <b>Liner Material:</b> HPPE <b>Cuff Style:</b> Knitwrist	13	7, 8, 9, 10, 11, 12, 13	Red	<ul style="list-style-type: none"> <li>• 10 pairs/bag, 6 bags/carton</li> </ul>

For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

#### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV  
Riverside Business Park  
Blvd International, 55  
1070 Brussels, Belgium  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

#### North America Region

Ansell Healthcare Products LLC  
111 Wood Avenue South,  
Suite 900  
Iselin, NJ 08830, USA  
T: +1 800 800 0444  
F: +1 800 800 0445

#### Australia

Ansell Limited  
Level 3,678 Victoria Street,  
Richmond, Vic, 3121  
Australia  
T: +61 1800 337 041  
F: +61 1800 803 578

#### Asia Pacific Region

Ansell Global Trading Center  
(Malaysia) Sdn Bhd  
Prima 6, Prima Avenue  
Block 3512, Jaijan Teknokrat 6  
T: +603 8310 6688  
F: +603 8310 6699

#### Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.  
Blvd. Bernardo Quintana No. 7001-C,  
Q7001 Torre II,  
Suites 1304, 1305 y 1306,  
Col. Centro Sur, c.p. 76079  
Queretaro, Qro. Mexico  
T: +52 442 248 1544 / 248 3133

#### Canada

Ansell Canada  
105 Lauder  
Cowansville, QC J2K 2K8  
Canada  
T: +1 800 363 8340  
F: +1 800 267 3551

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

