

TouchNTuff™

92-605

Extended Cuff Disposable Nitrile Glove
with Enhanced Chemical Splash
Protection

Long-cuffed disposable gloves, delivering superior chemical splash protection and comfort

- **World leader:** Extended-cuff version of TouchNTuff™ 92-600, the world's leading disposable gloves for chemical splash protection
- **Superior, extended cuff protection:** Made with TNT™ Chemical Splash Resistance Technology, these gloves guard hands, wrists and forearms against harmful chemical splashes
- **Elevated comfort:** Super soft nitrile provides a comfortable feel during extended wear
- **Robust durability:** Proprietary formulation is extra-strong to prevent tearing during heavy-duty work
- **Prevents surface defects:** Silicone-free, they prevent contaminant transfer that causes flaws in paints, coatings and finishes
- **Dermatest™ certified:** Supports reduced risk of skin irritation



Industries

- Life Sciences
- Food Processing
- Automotive

Recommended For

- Meat, Fish and Food Processing
- Industrial Production
- Sample taking and processing
- Transferring liquids and solids
- Laboratory analysis
- Maintenance
- Chemical Handling

TECHNICAL DATA SHEET

Product Information	
Material	Nitrile
External Glove Surface	Textured Fingers
Audit Standards	ISO 9001
Product Certification	ASTM D6319, Category III, EN ISO 21420:2020, EN ISO 374-1:2016 Type B JKPT, EN ISO 374-5:2016 Virus, EN 421:2010, FDA21 CFR 177-2600-US Food Contact Approved, EU Food Contact Approved, ISO 9001, ISO 18889:2019, UKCA, Dermatest
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Thailand
Product Segmentation	High Risk
Antistatic	Yes EN1149
Silicone Free	Yes


PHYSICAL PROPERTIES

	Typical Values		Testing Method
	BEFORE AGING	AFTER AGING	
Length (mm/inches)	300 / 12		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.12		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.2		ASTM D3767,EN 420
Elongation at Break (%)	≥ 500	≥ 400	ASTM D412
Force at break (N)	≥ 6	≥ 6	EN 455-2

ORDERING INFORMATION

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	92605070	92605080	92605090	92605100

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region

MY: +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

North America Region

Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region

BR: +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

Australia

Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia

Ansell PYC
Ten. +7 495 258 13 16

Technology



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

