

TouchNTuff™

93-250

Dark Grey Disposable Nitrile Glove with Ansell Grip™ Technology

Tough disposable hand protection offering superior wet, oily and dry grip

- **Reduces gripping effort:** Designed with ANSELL GRIP™ Technology, lab tests show 80% less finger force and 33% less palm force is required to hold objects when wearing these gloves
- **Superior durability and productivity:** The strong material helps increase productivity by preventing slippage when handling wet, dry or oily equipment in tough environments
- **Elevated comfort:** Soft nitrile enhances comfort when wearing gloves during long shifts
- **Prevents surface defects:** Silicone-free, they prevent contaminant transfer that causes flaws in paints, coatings and finishes
- **Reliable chemical splash protection:** TouchNTuff™ 93-250 gloves protect against accidental exposure to a range of acids, bases and solvents



Industries

- Automotive Aftermarket
- Life Sciences

Recommended For

- General Purpose Auto Aftermarket
- Spill or leakage cleanup
- Transferring liquids and solids
- Transferring liquids
- Sample taking and processing
- Product shipping, transport and delivery
- Testing
- Oil, fluids and filter change
- Engine transmission and repair
- Maintenance

TECHNICAL DATA SHEET

	Product Information
Material	Nitrile
External Glove Surface	Textured Fingers
Audit Standards	ISO 9001
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Portugal
Product Segmentation	Robust
Antistatic	Yes EN1149
Silicone Free	Yes


PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	245 / 9.65		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.13 / 5.1		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.20 / 7.9		ASTM D3767,EN 420
	BEFORE AGING	AFTER AGING	
Elongation at Break (%)	≥ 590	≥ 520	ASTM D412
Force at break (N)	≥ 10	≥ 9	EN 455-2

ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	93250060	93250070	93250080	93250090	93250100

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region
Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01
Asia Pacific Region
MY: +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

North America Region
Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445
Latin America & Caribbean Region
BR: +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

Australia
Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578
Russia
Ansell PYC
Ten. +7 495 258 13 16



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

